

Product Handling Information Sheet

Durostone[®] EPM 204

1. Company

| | |
|--------------|--|
| Name/Address | Röchling Industrial Nancy S.A.S. 8, Rue André Fruchard • 54520 B.P. 12, Maxéville/FR • Tel. +33 383 342424 info@roechling-permali.fr • www.roechling.com/industrial/nancy |
|--------------|--|

2. Product details

| | |
|-----------------------------------|---|
| Product/Article | Technical semi-finished product or machined part |
| Abbreviated terms | GFK-EP |
| Material Characterisation | Glass-fiber reinforced epoxy resin in hardened condition |
| Main Components | <ul style="list-style-type: none"> • glass-fiber • epoxy resin • stabiliser • additives |
| Components Subject to labelling | none |
| Classification according to REACH | Article |
| Notes | – |

3. Product characteristics

| | |
|------------------------------|--|
| Form/State | <ul style="list-style-type: none"> • firm |
| Color | – |
| Odour | <ul style="list-style-type: none"> • typical material smell |
| Density | – |
| Melting range | – |
| Glass transition temperature | – |



3. Product characteristics

| | |
|-----------------------|-------------------------|
| Thermal decomposition | None, with intended use |
| Flash point | – |
| Ignition temperature | – |
| Notes | – |

4. Danger warnings

| | |
|---|--|
| Special Risks For Mankind And The Environment | None |
| Notes | According to IARC glass fibre filaments cannot be classified as carcinogenic with humans (IARC group 3). The diameter of the glass fibre filaments which are used in this laminated material is outside of the lung-usual range from 3 μ m so that the danger of chronic lung damage is minimal. The diameter of the used glass fibre filaments amounts to 5 – 16 μ m (typical 12 μ m). Their diameter is not reduced by treatment of these fibres, i. e. it's potential lung freedom of movement does not increase. |

5. Handling and Storage

| | |
|-----------------|--|
| Handling | <ul style="list-style-type: none"> • Product can be worked with conventional machines and tools. • For the machining special tools should be used such as tungsten carbides drill / PKD or diamond-equipped tools. |
| Storage | <ul style="list-style-type: none"> • horizontally • dry • protected against climatic influences |
| Safety measures | <ul style="list-style-type: none"> • Provide effective dust extraction when processing and machining. • Carry protective mask and eye protector with dusty condition. |
| Shelf Life | – |
| Notes | – |

6. Transport

| | |
|--------------------------|---|
| Transport | <ul style="list-style-type: none"> • Non dangerous goods according to the transport regulations. • Secure against slipping. |
| Finished Product Packing | – |



6. Transport

Notes –

7. Fire – fighting measures

Suitable extinguishing agents

- water
- sand
- foam
- CO₂

Potential combustion products

- CO
- CO₂
- carbon monoxide
- other toxic gases

Necessary protection equipment

- Complete protection equipment for fire-brigade.
- Use self-contained air respirators during strong smoke and steam development.

Notes –

8. Removal

Recyclability Check possibility of recycling.

EC Waste Catalog The product is classified in accordance with the European-Waste Catalogue (EWC) as “not dangerous”.

Waste Removal Can be recycled and/or has to be conveyed to a suitable dump or a suitable combustion plant.

EC Waste Code

- 10 11 03 waste glass-based fibrous materials

Notes –

9. Marking and Guidelines

Marking in accordance with EEC Guideline no labelling required

Notes –

10. Information about REACH



Information about REACH

According to EC directive 1907/2006/EC (REACH), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACH), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACH we are manufacturing articles and, therefore, not required to issue safety sheets.

11. Other Information

Other Information

–

