

Product Handling Information Sheet

Astrawood[®] COOL colored decor

1. Company	
Name/Address	Röchling Industrial SE & Co. KG - Troisdorf
	Mülheimer Str. 26 - Geb. 115 • 53840 Troisdorf/DE • Tel. +49 2241 4820-0
	info@roechling-plastics.com • www.roechling.com/industrial/troisdorf
2. Product details	
Product/Article	Technical semi-finished product or machined part
Abbreviated terms	PVC-U
Material Characterisation	Amorphous plastic
Main Components	polyvinyl chloridestabiliseradditive
Components Subject to labelling	ng –
Classification according to REA	ACh Article
Notes	
3. Product characteristics	
Form/State	
	• firm
Color	colored decor
Odour	nearly odourless
Density	1,41
Melting range	_
Glass transition temperature	_
Thermal decomposition	>180°C





	_		
	>450°C		
and The	None		
	_		
	 Product can be worked with conventional machines and tools. Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions. While the processing sufficient for enough airing or by smoke attack provide for a extraction. 		
	 horizontally dry protected against frost protected against climatic influences do not store with flammable materials 		
	_		
	By the processing under high temperatures gases can outcome, these gases can cause irritation the eyes and respiratory tract. The protective film must be removed immediately after installation.		
	 Non dangerous goods according to the transport regulations. Secure against slipping. 		
	_		
	_		
	and The		





7. Fire – fighting measures	3		
Suitable extinguishing agents		water mistfoamdry extinguishing media	
Potential combustion products		hydrofluoric acidcarbon monoxidehydrocarbon	
Necessary protection equipment		 Complete protection equipment for fire-brigade. Use self-contained air respirators during strong smoke and steam development. 	
Notes		Molten product has to be cooled with water. Fire residues must be collected and disposed of according to the local instruction.	
8. Removal			
Recyclability		Check possibility of recycling.	
EC Waste Catalog		The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".	
Waste Removal		Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.	
EC Waste Code		12 01 05 plastics shavings and turnings20 01 39 plastics	
Notes		This material can to 100 % be recycled.	
9. Marking and Guidelines			
Marking in accordance with	EEC Guidelin	ne no labelling required	
Notes			
10. Information about REA	Ch		
Information about REACh		According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets	





11. Other Information			
Other Information	The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.		



