

Product Handling Information Sheet

Polystone® PVDF natural extruded

1. Company		
Name/Address		Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren
2. Product details		
Product/Article		Technical semi-finished product or machined part
Abbreviated terms		PVDF
Material Characterisation		Semi crystalline plastic
Main Components		polyvinylidene fluoride
Components Subject to labelling		none
Classification according to REAC	h	Article
Notes		
3. Product characteristics		
Form/State		• firm
Color		natural
Odour		nearly odourless
Density		>1,75
Melting range		172 175
Glass transition temperature		-
Thermal decomposition		> 350°C
Flash point		-
Ignition temperature		-





3. Product characteristics	
Notes	
4. Danger warnings	
Special Risks For Mankind A Environment	nd The none
Notes	
5. Handling and Storage	
Handling	 Product can be worked with conventional machines and tools. Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions. When welding do not exceed the recommended air and tool temperatures. By disregarding the instructions the staff can falls in Fluor fever (fever with flu-like symptoms). At the first sign a doctor should be consulted. Plant parts should be grounded. Carry out processing in such a way that there is no thermal decomposition.
Storage	 horizontally dry protected against frost protected against climatic influences
Safety measures	 In case of inhalation of decomposition products: - Take to fresh air.
Shelf Life	-
Notes	
6. Transport	
Transport	Non dangerous goods according to the transport regulations.Secure against slipping.
Finished Product Packing	-
Notes	-





7. Fire – fighting measures	
Suitable extinguishing agents	 water foam CO₂ dry powder extinguishing agents
Potential combustion products	hydrofluoric acidCOlow molecular fluorocarbon
Necessary protection equipment	 Complete protection equipment for fire-brigade. Use self-contained air respirators during strong smoke and steam development.
Notes	Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.
8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) a "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance wit local regulations.
EC Waste Code	12 01 05 plastics shavings and turnings20 01 39 plastics
Notes	-
9. Marking and Guidelines	
Marking in accordance with EEC	Guideline no labelling required
Notes	The material does not contain constituents that exhibit endocrine disrupting properties in quantities of 0.1% or more in accordance with REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605.

10. Information about REACh







Information about REACh

According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.-

11. Other Information

Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.



