

## Product Handling Information Sheet

### Sustanat® PC GF 20 natural

#### 1. Company

Name/Address **Röchling Industrial Lahnstein SE & Co. KG**  
 Sustaplast-Str. 1 • 56112 Lahnstein/Germany (DE) • Tel. +49 2621 693-0  
 info.lahnstein@roechling.com • www.roechling.com/industrial/lahnstein

#### 2. Product details

Product/Article Engineering semi-finished product

Abbreviated terms PC

Material Characterisation Thermoplastic

Main Components

- polycarbonate
- contains glass fibre
- evtl. colour pigments

Components Subject to labelling none

Classification according to REACH Article

Notes –

#### 3. Product characteristics

Form/State

- solid

Color natural

Odour

- odourless

Density 1,33

Melting range -

Glass transition temperature 150

Thermal decomposition >380 °C



### 3. Product characteristics

Flash point	-
Ignition temperature	>450 °C
Notes	-

### 4. Danger warnings

Special Risks For Mankind And The Environment	none
Notes	-

### 5. Handling and Storage

Handling	<ul style="list-style-type: none"> <li>• Product can be worked with conventional machines and tools.</li> <li>• Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.</li> </ul>
Storage	<ul style="list-style-type: none"> <li>• horizontally</li> <li>• dry</li> <li>• protected against climatic influences</li> </ul>
Safety measures	-
Shelf Life	-
Notes	-

### 6. Transport

Transport	<ul style="list-style-type: none"> <li>• Not classified as hazardous good under transport regulations.</li> </ul>
Finished Product Packing	-
Notes	-

### 7. Fire – fighting measures

Suitable extinguishing agents	<ul style="list-style-type: none"> <li>• water</li> <li>• foam</li> <li>• dry extinguishing media</li> <li>• CO<sub>2</sub></li> </ul>
Potential combustion products	<ul style="list-style-type: none"> <li>• carbon monoxide</li> <li>• aliphatic</li> <li>• aromatic hydrocarbon</li> <li>• aldehyde</li> <li>• acids</li> <li>• phenol</li> <li>• phenol derivate</li> </ul>
Necessary protection equipment	<ul style="list-style-type: none"> <li>• Fire fighters and others exposed to combustion products should wear full protective clothing and self-contained breathing apparatus.</li> </ul>
Notes	Molten product should be cooled by water spray. Dispose fire debris and contaminated extinguishing water in accordance with local regulations.

### 8. Removal

Recyclability	Check possibility of recycling.
EC Waste Catalog	According the European waste catalogue (EAK) the product is not classified as hazardous.
Waste Removal	Waste disposal by landfill or incineration in compliance with state and local regulations.
EC Waste Code	<ul style="list-style-type: none"> <li>• 12 01 05 plastics shavings and turnings</li> <li>• 07 02 13 waste plastic</li> </ul>
Notes	–

### 9. Marking and Guidelines

Marking in accordance with EEC Guideline	not subject to labelling
Notes	–

### 10. Information about REACh



### Information about REACH

According to EC directive 1907/2006/EC (REACH), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACH), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACH we are manufacturing articles and, therefore, not required to issue safety sheets.-

### 11. Other Information

#### Other Information

All above mentioned information are based on our current state of knowledge and ensure no warranty of quality. Existing laws and regulations have to be observed by the recipient of our products on his own authority.

