

Product Handling Information Sheet Sustarin[®] C yellow

1. Company				
Name/Address	Röchling Industrial Lahnstein SE & Co. KG Sustaplast-Str. 1 • 56112 Lahnstein/Germany (DE) • Tel. +49 2621 693-0			
	info.lahnstein@roechling.com • www.roechling.com/industrial/lahnstein			
2. Product details				
Product/Article	Engineering semi-finished product			
Abbreviated terms	POM-C			
Material Characterisation	Thermoplastic			
Main Components	 polyacetal copolymer contains evtl. colour pigments			
Components Subject to labelling	none			
Classification according to REACh	Article			
Notes				

3. Product characteristics		
Form/State	• solid	
Color	yellow	
Odour	odourless	
Density	1,41	
Melting range	165	
Glass transition temperature		
Thermal decomposition	>240 °C	
Flash point		



Röchling

Industrial

Ignition temperature	>320 °C			
Notes				
4. Danger warnings				
Special Risks For Mankind And Tr Environment	ie none			
Notes				
5. Handling and Storage				
Handling	 Product can be worked with conventional machines and tools. Before machining the product should have room temperature and/or to be stored fo min. 24h under normal climatic conditions. 			
Storage	 horizontally dry protected against climatic influences 			
Safety measures				
Shelf Life	-			
Notes	-			
6. Transport				
Transport	 Not classified as hazardous good under transport regulations. 			
Finished Product Packing	-			
Finished Floudel Facking				

7. Fire – fighting measures	
Suitable extinguishing agents	waterfoamdry extinguishing media



Print: 16/06/2025 • Release: 20/09/2023 • Version: 4.0 PIM-Version: 896 • PIM-ID: 591079 • PIM-Code: 896-29

Röchling

7. Fire – fighting measures	
Potential combustion products	 carbon monoxide formaldehyde – formation of further fission and oxidation products depend upon the fire conditions (traces of any other toxic substances can not be excluded)
Necessary protection equipment	• Fire fighters and others exposed to combustion products should wear full protective clothing and self-contained breathing apparatus.
Notes	Molten product should be cooled by water spray. Dispose fire debris and contaminated extinguishing water in accordance with local regulations.

8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	According the European waste catalogue (EAK) the product is not classified as hazardous.
Waste Removal	Waste disposal by landfill or incineration in compliance with state and local regulations.
EC Waste Code	12 01 05 plastics shavings and turnings07 02 13 waste plastic
Notes	-

9. Marking and Guidelines					
Marking in accordance with E	EC Guideline	not subject to I	abelling		
Notes		-			

10. Information about REACh	
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets

11. Other Information	
Other Information	All above mentioned information are based on our current state of knowledge and ensure no warranty of quality. Existing laws and regulations have to be observed by the recepient of our products on his own authority.



Print: 16/06/2025 • Release: 20/09/2023 • Version: 4.0 PIM-Version: 896 • PIM-ID: 591079 • PIM-Code: 896-29