

Product Handling Information Sheet

Trovidur® EC Clad white

1. Company	
Name/Address	Röchling Industrial SE & Co. KG - Troisdorf Mülheimer Str. 26 - Geb. 115 • 53840 Troisdorf/DE • Tel. +49 2241 4820-0 info@roechling-plastics.com • www.roechling.com/industrial/troisdorf
	The Greech and place to the control of the control
2. Product details	
Product/Article	Technical semi-finished product or machined part
Abbreviated terms	PVC-U
Material Characterisation	Thermoplastic
Main Components	polyvinyl chloridestabiliseradditive
Components Subject to labelling	ng –
Classification according to RE.	ACh Article
Notes	
3. Product characteristics	
Form/State	• firm
Color	white
Odour	nearly odourless
Density	1,44
Melting range	<u>-</u>
Glass transition temperature	-
Thermal decomposition	> 180°C





3. Product characteristics			
Flash point		_	
Ignition temperature		> 450°C	
Notes			
4. Danger warnings			
Special Risks For Mankind And The Environment		none	
Notes		_	
5. Handling and Storage			
Handling		 Product can be worked with conventional machines and tools. Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions. While the processing sufficient for enough airing or by smoke attack provide for a extraction. 	
Storage		 horizontally dry protected against frost protected against climatic influences do not store with flammable materials 	
Safety measures			
Shelf Life			
Notes		By the processing under high temperatures gases can outcome, these gases can cause irritation the eyes and respiratory tract. The protective film must be removed immediately after installation.	
6. Transport			
Transport		 Non dangerous goods according to the transport regulations. Secure against slipping. 	
Finished Product Packing			
Notes			





7. Fire – fighting measures	
Suitable extinguishing agents	water mistfoamdry powder extinguishing agents
Potential combustion products	 carbon monoxide CO₂ hydrochloric acid hydrocarbon
Necessary protection equipmer	Complete protection equipment for fire-brigade.
Notes	Molten product has to be cooled with water. Fire residues must be collected and disposed of according to the local instruction.
8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	12 01 05 plastics shavings and turnings20 01 39 plastics
Notes	This material can to 100 % be recycled.
9. Marking and Guidelines	
	C Guideline no labelling required
Notes	-
10. Information about REACh	
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets





11. Other Information				
Other Information	The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.			



