

## Technical Data Sheet

# Fibracon<sup>®</sup> PTFE + 5% MoS2

### Typical characteristics

- Increased hardness
- Minimal effect on chemical and electrical properties
- High stiffness

### Typical industries

- 化学处理行业
- 车辆构造
- 电子
- 石油和天然气
- 机械工程行业
- Healthcare
- 食品行业
- 风能

	Test method	Unit	Guideline value
<b>General properties</b>			
Density	ASTM D4894	g / cm <sup>3</sup>	2.22 +/- 0.03
<b>Mechanical properties</b>			
Shore hardness	DIN EN ISO 868	Shore D	56-58
Tensile Strength	ASTM D4894	MPa	30
Elongation	ASTM D4894	%	300
<b>Thermal properties</b>			
Service Temperature		°C	-200 to +260

This data provides typical values on a small selection of properties of the material and should only be used as a guide to the generic material performance.

### Röchling Industrial (UK) Ltd. – High Peak

Bowden Hey Road - Chapel-en-le-Frith • SK23 0QZ High Peak, Derbyshire/United Kingdom (GB) • Tel. +44 1298 811 800  
 info@roechling-fibracon.co.uk • www.roechling.com/industrial/high-peak

Print: 04/05/2024 • Release: 20/09/2023

PIM-Version: 34 • PIM-ID: 709623 • PIM-Code: 34-40-9.8.131-7.6.8.5.5.9.5.10-1

